
EZ FABRIC CURVED DOUBLE COUNTER









PRODUCT CODE: EZ-CRVFABCTR-G2





Screw & Wingnut Frame Connection




PRODUCT DESCRIPTION

Double your counter space! Two aluminum counter frames connect together using four screws with wing nuts to secure. Push button snaps connect the lightweight aluminum framework together. One graphic covers the double counter! Position the frame inside the fabric graphic, pullover to fully cover frame, then zip shut the backside. Attach countertop. Graphics available on front, back, sides and top. See your printed graphic through the frosted acrylic countertop piece! Carry bag included. Wooden shelf inserts optional.

DISPLAY DIMENSION	81" W x 38" H x 29.5" L	
GRAPHIC DIMENSIONS	123.25" W x 40" H	
GRAPHIC MATERIAL		
Stretch Fabric		
GRAPHIC FINISHING		
One piece. Inside hem. Two top zippers.		
DISPLAY CONSTRUCTION		
Aluminum Frame	Acrylic Counter Top	
SHIPPING WEIGHTS & DIMENSIONS		
Shipping Weight	51 lbs (2 frames only) 53 lbs (2 frames with graphic)	
Shipping Dimensions	50" H x 21" W x 14" D	
LARGE QUANTITY FREIGHT		
Freight Shipping	15 boxes per 49" L x 40" W x 75" H skids	
Freight Weight	810 lbs (2 frames only) 840 lbs (2 frames & graphic)	
GRAPHIC TURN AROUND TIME		
2 business days after proof approval		
AVAILABLE ACCESSORIES		
Curved Shelf		
AVAILABILITY		CA and PA
TOP WEIGHT CAPACITY		75 lbs
SHELF WEIGHT CAPACITY		7 lbs



PRODUCT CODE: EZ-CRVFABCTR-G2







Qty 8 - 33" Vertical Support Bar




Qty 2 - Acrylic Top Counter



Qty 4 - Screw & Wingnut



Qty 2 - Bottom Base



Qty 4 - 13.25" Horizontal Support Bar



Qty 4 - Large Head Bolt

REQUIRED TOOLS



Then screw and tighten.

PRODUCT CODE: EZ-CRVFABCTR-G2

SET UP INSTRUCTIONS 1/2

Step 1

First, start by building both vertical sides of the EZ Fabric Counter.



Step 3

Set out your bottom base on a flat surface. Be sure not to confuse this base with the top, which has (2) pre-drilled holes for the acrylic counter top. Locate the push-out caps on the inside of the posts.



Step 5

The frame is now ready for the top base. Make sure it appears as shown above.



Step 7

Be sure that there is (1) pre-drilled hole on each side, facing up on the top base.



Step 2

Take (2) 33"support bars and (1) 13.25" support bar and connect them as shown above. Repeat the same process for another set.



Step 4

Push in and then hold the push-out cap on the bottom base so the support bar will slide an. Now slide each bar completely on to the bottom base. You will slide in one push-out cap at a time.



Step 6 Slide on the top base just as mentioned in step 4.



Step 8 Complete the first frame.



SET UP INSTRUCTIONS 2/2

Step 9

Repeat same process for second frame and place frames side by side.



Step 11

Starting from the bottom, slide the graphic on to the frame.




Step 13

Locate the pre-drilled hole on the top base. Make sure this hole aligns with the finished hole on the graphic.



Step 10

Connect frames with bolts and wing nuts.



Step 12 Zip up the graphic around the frame.



Step 14

Align the acrylic counter top holes and insert the large head screws to secure the counter top to the frame.



Step 15

The install is now complete.

